BOTTOM HOLE ASSURANCE, INC.

Blacklight, Ultrasonic Wall Thickness, & Liquid Penetrant Inspection

Email: BHAInc@bottomholeassurance.com
109 Citron Drive • Youngsville, LA 70592
Office: (337) 857-8994 Fax: (337) 857-8964

No. DIR 43658-1

CUSTOMER HOLE OPENER CORP ☐ 3RD PARTY
RIG
OCS-G & WELL
FACILITY / LOCATION SHOP
PROJECT STONE HILL MARTIN IRA 30944
AUTHORIZED BY DONOVAN
P.O. / JOB #
INVOICE NO. 43658
DATE: 4/10/2021

								PIN										BOX											
Serial #	Tool Description	Overall Length	Fishing Neck Length	Tong Space	Pin I.D.	Pin O.D.	Box O.D.	Connection Size	Pin Length	Pin Cylinder Diameter	Pin Nose Diameter	Pin Relief Diameter	Pin Rel. Width Pin Neck Lgth	Bevel Diameter	B S R	OK or Reject	Remarks	Connection Size	Counter Bore Length	Counter Bore Diameter	Bore Back Dia. Float Bore Dia.	Bore Back Lgth Float Bore Lgth	Box Thread Length	Counterbore Wall Thickness	Bevel Diameter	B S R	OK or Reject	Remarks
DTU-07-950-3	9 1/2 UNDER REAMER BODY	5.42			N/A	9 1/2	8 1/2	INT (B) INT								OK OK		6 5/8 REG	11/16	6 1/16					7 11/32	N/A	OK	
TS-07-950-1	TOP SUB	3.13	12 1/2	24"	3"	8"	9 1/2	6 5/8 REG	4 15/16				5/16	7 1/2		OK		INT									OK	
05-950-011-018,019,038	(3) HINGE BLOCK															OK (3)												
05-950-010-002,003,004	(3) HINGE BLOCK															OK (3)												
05-950-012-013,019,012	(3) HINGE PIN															OK (3)												
05-950-007-003	PISTON							INT								OK												
05-950-008-006	STOP PIPE							INT								OK												
05-950-005-008	YOKE																	INT									OK	
05-950-006-002	FLOW TUBE															OK												
05-117-009-001	BUSHING															OK												

Remarks: FULL BODY INSP AS PER DS-1 VOL 4

Customer Rep Signoff:

Batch # Info.
20-B 20B065
Dry Powder 130531
7-HF
White Contrast
14-A

Connection Inspection
Wet Flour. M.P.I. ☑ Dry M.P.I ☐
Vis. Liq. Pen. ☐ Residual ☐
Flour Liq. Pen. ☐ Continuous ☑
Long. Insp. ☐ AC Current ☐
Trans. Insp. ☑ DC Current ☑

Body Inspection
Wet Flour. M.P.I. ☑ Residual ☐
Vis. Liq. Pen. ☐ Continuous ☑
Flour Liq. Pen ☐ AC Current ☐
Long. Insp. ☐ DC Current ☑
Trans. Insp. ☑ Visible M.P.I ☐

Body Dry M.P.I
Dry M.P.I ☑ Residual ☐
Long. Insp. ☑ Continuous ☑
Trans Insp. ☐ AC Current ☑
DC Current ☐

Blacklight Inspection
Blacklight Intensity 5135 Bath Mixture: 025 Whitelight 0.1

Equipment / Inspector Information
Equipment Used From Unit # 25
Qual. Date(s) MT 5/6/2019 PT
Level II Inspector: TANNER BLANCHARD
Signature:
Signature guarantees final walk thru of job and job site

Liquid Penetrant Inspection
Magnaflux Developer: SKD S2
Batch #
Dwell Time min
White Light
Magnaflux Penetrant (Check one) ☐ SKL-WP2 ☐ ZL-60D
Batch #
Dwell Time: min

System Effectiveness: LP-Comparitive Block ☐ Dry MP-Castrol Strip ☑ Wet MP-Castrol Strip ☑ Profile Gage RSC OK ☑

Job Information
B TB V TB D P TB

3rd Party Rep
Signature:

E-DIR01-05